

TG SERIES

The most reliable ozone generators on the market.

MANY OPTIONS AVAILABLE TO FIT YOUR EXACT SPECIFICATIONS.





FEATURES OF TG SERIES:

EATURES

- 0 to 600 g/hr ozone production
- Adjustable electrical potentiometer 0-100%
- Low oxygen demand for ozone output
- Microprocessor features safety protections
- Can integrate with PLC or computers (option)
- 10-80 PSI capabilities
- Available for rent or purchase

TG-SERIES OZONE GENERATORS

System Sizes

Model	Max Rated Ozone Output	Rated Oxygen Flow	Ozone Production	Cooling	Power Consumption
TG-10	10 g/hr	0-10 LPM	10 g/hr at 4.5% from 3 LPM oxygen	Air	150 watts
TG-20	20 g/hr	0-10 LPM	20 g/hr at 5.0% from 5 LPM oxygen	Air	300 watts
TG-40	40 g/hr	0-10 LPM	40 g/hr at 4.7% from 10 LPM oxygen 30 g/hr at 6% from 6 LPM oxygen	Air	400 watts
TG-75	75 g/hr	0-15 LPM	60 g/hr at 8.2% from 10 LPM oxygen 75 g/hr at 5.8% from 15 LPM oxygen	Water	600 watts
TG-150	150 g/hr	0-30 LPM	150 g/hr at 5.8% from 30 LPM oxygen 70 g/hr at 8.2% from 10 LPM oxygen	Water	1200 watts
TG-300	300 g/hr	0-60 LPM	300 g/hr at 5.8% from 60 LPM oxygen 140 g/hr at 8.2% from 30 LPM oxygen	Water	2400 watts
TG-450	450 g/hr	0-90 LPM	450 g/hr at 5.8% from 90 LPM oxygen 290 g/hr at 7.5% from 45 LPM oxygen	Water	3600 watts
TG-600	600 g/hr	0-120 LPM	600 g/hr at 5.8% from 120 LPM oxygen 390 g/hr at 7.5% from 60 LPM oxygen	Water	4800 watts

Optional Accessories	Description		
Flowmeter	0-10 LPM, 0-20 LPM Acrylic Flowmeter or High Accuracy 0-10 LPM Aluminum Flowmeter (which is best for precise flow control).		
Pressure Gauge	0-30PSI or 0-60 PSI that displays corona cell pressure.		
Input	4-20 mA Input or 0-10 Vault Input allows you to control the generator output remotely.		

CONTACT US FOR MORE INFORMATION



Ozone Solutions, Inc. 451 Black Forest Road • Hull, IA 51239 Tel: 1.712.439.6880 | Fax: 1.712.439.6733

Visit us on the web: www.ozonesolutions.com

